



Industry Bearing No.	Inside Diameter (d)		Outside Diameter (D)		Width (W)		Radius (r)	Basic Load Rating (lbs.)	
	mm	inch	mm	inch	mm	inch	mm	Dynamic C	Static C <sub>0</sub>
6300	10	.3937	35	1.3780	11	.4331	1.0	1840	785
6301	12	.4724	37	1.4567	12	.4724	1.5	2180	940
6302	15	.5906	42	1.6535	13	.5118	1.5	2570	1220
6303	17	.6693	47	1.8504	14	.5512	1.5	3050	1470
6304	20	.7874	52	2.472	15	.5906	2.0	3600	1770
6305	25	.9843	62	2.4409	17	.6693	2.0	4750	2460
6306	30	1.1811	72	2.8346	19	.7480	2.0	6000	3400
6307	35	1.3780	80	3.1496	21	.8268	2.5	7500	4300
6308	40	1.5748	90	3.5433	23	.9055	2.5	9150	5400
6309	45	1.7717	100	3.9370	25	.9843	2.5	11900	7200
6310	50	1.9685	110	4.3307	27	1.0630	3.0	13900	8600
6311	55	2.1654	120	4.7244	29	1.1417	3.0	16100	10100
6312	60	2.3622	130	5.1181	31	1.2205	3.5	18400	11700
6313	65	2.5591	140	5.5118	33	1.2992	3.5	20800	13400
6314	70	2.7559	150	5.9055	35	1.3780	3.5	23400	15300
6315	75	2.9528	160	6.2992	37	1.4567	3.5	25500	17400
6316	80	3.1496	170	6.6929	39	1.5354	3.5	27600	19500
6317	85	3.3465	180	7.0866	41	1.6142	4.0	29800	21800
6318	90	3.5433	190	7.4803	43	1.6929	4.0	32000	24100
6319	95	3.7402	200	7.8740	45	1.7717	4.0	34500	26600
6320	100	3.9370	215	8.4646	47	1.8504	4.0	39000	31500
6321	105	4.1339	225	8.8583	49	1.9291	4.0	41500	34500
6322	110	4.3307	240	9.4488	50	1.9685	4.0	40000	40500
6324	120	4.7244	260	10.2362	55	2.1654	4.0	46500	41500